

High quality components ...



... in an industrial design.

## Main characteristics

- Capacity: 2500 kg/24 h flake ice chipped type
- Ideal ice temperature of  $-0,5\text{ }^{\circ}\text{C}$   
Macrolce, StandardIce or Microlce
- Designed for continuous operation -  
24 hours - 7 days a week
- Hygienic Design: Closed watersystem -  
protected against contamination by external influences
- Environmental friendly technology -  
No moving parts in the refrigeration circuit of the  
evaporator-  
no refrigerant leakage



Macrolce




StandardIce



Microlce

## Dimensions and connections



- A control panel
- C ice discharge
- D electr. connection
- E water supply
- F water drain

provided by customer:  
water filter  
stop cock  
electr. protection  
waste water connection  
(contactless)

## Technical Data

	UBE 2.500 20°C	UBE 2.500 35°C
2500 kg/24 h nominal capacity at	20 °C air temperature and 15 °C water temperature	35 °C air temperature and 25 °C water temperature
frame dimensions (L x W x H)	131 cm x 131 cm x 141 cm	131 cm x 131 cm x 141 cm
weight	700 kg	750 kg
frame and cover panels	powder coated	powder coated
ice discharge	see specification "ice discharges"	see specification "ice discharges"
electricity		
power consumption	9,3 kW	10,3 kW
current consumption	19,5 A	24 A
provided by customer		
electric supply	3/N/PE ~ 400V 50Hz	3/N/PE ~ 400V 50Hz
fuse, slow-blow	50 A	50 A
cable cross section, Cu	6 mm <sup>2</sup>	6 mm <sup>2</sup>
water		
supply / drain	1/2 " / 14 mm	1/2 " / 14 mm
provided by customer		
pressure	2 - 5 bar	2 - 5 bar
quality	drinking water	drinking water
pH-value	7,2 - 9,5 pH	7,2 - 9,5 pH
hardness	6 - 14 °dH	6 - 14 °dH
temperature	100 - 250 mg CaCO <sub>3</sub> /l 5 °C - 30 °C	100 - 250 mg CaCO <sub>3</sub> /l 5 °C - 30 °C
ambient temperature	5 °C - 42 °C	5 °C - 45 °C
condenser	air cooled	air cooled
air flow	7200 m <sup>3</sup> /h	7200 m <sup>3</sup> /h
heat emission	20 kW	20,5 kW
refrigerant R452A / R404A	8 kg	9 kg
compressor	semi-hermetic 4NES-14Y PW Bitzer	semi-hermetic 4HE-18Y PW Bitzer
refrigerating capacity	12,5 kW	13,8 kW
evaporation temperature	-32 °C	-31 °C
condensation temperature	33 °C	45 °C
noise level	73 dBA (3 m)	76 dBA (3 m)

Subject to technical modifications. In case of deviations please contact us.

## Scope of supply

The ZIEGRA ice machine will be delivered according to CE standards and ready for connection to water and electricity.

### ZIEGRA quality and reliability

- HygienePlus: automatic water drain for additional hygiene
- Condensation control in order to keep an equally high ice quality
- 5 min. overrun to use the re-evaporation after switch-off
- Phase sequence relay
- Overload cut-out / thermal switch for all motors and the compressor
- High / Low pressure control
- Water level monitoring
- Ice discharge hose or discharge tube, according to requirements.
- Switch-off by light scanner or light barrier when ice bin or recipient is full.
- For a wide range of accessories such as storage bins, or water treatment see separate list "options and accessories"

## Options


- Ice discharges in various designs, e.g. to produce
  - into a storage bin, or
  - into an ice trolley or similar
- Condenser either blowing upwards or sideways
- Split installation, e.g. condenser, refrigeration unit or both in remote version
- For connection to cooling water
- Low-noise condenser (only for remote installation)
- Ice maker only
  - for separate refrigeration unit
  - for central refrigeration system
- Stainless steel frame or cabinet, or without cabinet
- Special voltage



Ice maker with control system and stainless steel cabinet...

## Accessories

- Ice storage bins in various sizes and designs, suitable for integration into automated processes e.g. AS, S for automatic or manual dosing
- HygienePlus: flushing system or flushing incl. disinfection
- Cartridge Water Filter reduces lime scale and germs
- UV sterilization
- ZIEGRA water softening: available for very hard water and large flow rates
- Support, wall brackets, or similar
- Melt water pump, leak water sensor and leak water tray
- Freeze protection
- additional separate operating switch
- timer for 7 days
- protection against overvoltage and undervoltage
- Spare parts available for minimum for 15 years
- Global sales and service.



Silo AS 500 with ice machine



Cartridge waterfilter 180-2

Technical details: please see respective machine specification. With pleasure we submit to you any further information, also regarding your special requirements